

# Auto Multiport Valve

**RELI  
POWER**<sup>®</sup>  
RELIABLE POWER



EXTERNAL  
POWER ADAPTOR



TIME MODE



INBUILT TOP  
STRAINER



COMPATIBLE  
WITH RO PANELS



## Specifications

Model	RF-5T-T	RF-3T-T
Type	Filter	Filter
Mode of operation	Automatic	Automatic
Installation position	Top Mounted	Top Mounted
Water capacity (Maximum)	5000 LPH	3000 LPH
Size of inlet/outlet	1" F	3/4" F
Size of drain	1" F	3/4" F
Size of riser pipe	32 mm OD	26.7 mm OD
T & B strainer size	1 "	3/4 "
Size of base	2.5"	2.5 "

## Electrical Parameter

Input Voltage	12V	12V
Current	0.6A	0.6A
Power Rating	8W	8W
Relay Contact	5A (Max.)	5A (Max.)

## Application

- Iron Removal Filter
- Sand Filter
- Carbon Filter
- Residential
- Swimming Pool
- Commercial

Tel No : +91-41106124,45066467.

Email Id : [info@purensafe.com](mailto:info@purensafe.com) / Website : [www.purensafe.com](http://www.purensafe.com)

# Auto Multiport Valve

**RELI  
POWER**<sup>®</sup>  
RELIABLE POWER



EXTERNAL  
POWER ADAPTOR



METER MODE



INBUILT TOP  
STRAINER



COMPATIBLE  
WITH RO PANELS



## Specifications

Model	RF-5T-M	RF-3T-M
Type	Filter	Filter
Mode of operation	Automatic	Automatic
Installation position	Top Mounted	Top Mounted
Water capacity (Maximum)	5000 LPH	3000 LPH
Size of inlet/outlet	1" F	3/4" F
Size of drain	1" F	3/4" F
Size of riser pipe	32 mm OD	26.7 mm OD
T & B strainer size	1 "	3/4 "
Size of base	2.5"	2.5 "

## Electrical Parameter

Input Voltage	12V	12V
Current	0.6A	0.6A
Power Rating	8W	8W
Relay Contact	5A (Max.)	5A (Max.)

## Application

- Iron Removal Filter
- Sand Filter
- Carbon Filter
- Residential
- Swimming Pool
- Commercial

Tel No : +91-41106124,45066467.

Email Id : [info@purensafe.com](mailto:info@purensafe.com) / Website : [www.purensafe.com](http://www.purensafe.com)

# Auto Multiport Valve

**RELI  
POWER**<sup>®</sup>  
RELIABLE POWER



EXTERNAL  
POWER ADAPTOR



METER MODE



FLOW METER



BRINE  
ASSEMBLY



COMPATIBLE  
WITH RO PANELS



## Specifications

Model	RS-5T-M	RS-3T-M
Type	Softener	Softener
Mode of operation	Automatic	Automatic
Installation position	Top Mounted	Top Mounted
Water capacity (Maximum)	5000 LPH	3000 LPH
Size of inlet/outlet	1" F	3/4" F
Size of drain	1" F	3/4" F
Size of riser pipe	32 mm OD	26.7 mm OD
T & B strainer size	1 "	3/4 "
Size of base	2.5"	2.5 "

## Electrical Parameter

Input Voltage	12V	12V
Current	0.6A	0.6A
Power Rating	8W	8W
Relay Contact	5A (Max.)	5A (Max.)

## Application

- Domestic • Hospital • Restaurant
- Ion Exchange • Commercial • Swimming Pool

Tel No : +91-41106124,45066467.

Email Id : [info@purensafe.com](mailto:info@purensafe.com) / Website : [www.purensafe.com](http://www.purensafe.com)

# Auto Multiport Valve

**RELI  
POWER**<sup>®</sup>  
RELIABLE POWER



EXTERNAL  
POWER ADAPTOR



TIME MODE



BRINE ASSEMBLY



COMPATIBLE  
WITH RO PANELS



## Specifications

Model	RS-5T-T	RS-3T-T
Type	Softener	Softener
Mode of operation	Automatic	Automatic
Installation position	Top Mounted	Top Mounted
Water capacity (Maximum)	5000 LPH	3000 LPH
Size of inlet/outlet	1" F	3/4" F
Size of drain	1" F	3/4" F
Size of riser pipe	32 mm OD	26.7 mm OD
T & B strainer size	1 "	3/4 "
Size of base	2.5"	2.5 "

## Electrical Parameter

Input Voltage	12V	12V
Current	0.6A	0.6A
Power Rating	8W	8W
Relay Contact	5A (Max.)	5A (Max.)

## Application

- Domestic • Hospital • Restaurant
- Ion Exchange • Commercial • Swimming Pool

Tel No : +91-41106124,45066467.

Email Id : [info@purensafe.com](mailto:info@purensafe.com) / Website : [www.purensafe.com](http://www.purensafe.com)